



MAX SERIES

ALL-IN-ONE

The Max Series accommodates "All-in-one" design philosophy, integrating battery with longevity, intelligent BMS, high performance PCS, preventive safety system, smart distribution system and heat dissipation management system into one standard container for standardized manufacturing and simpler installation.



Safe



Economic



Intelligent



Augmentable

Features

- **Safe:** Compartmentalization design with preventive alarming system
- **Economic:** Zero power loss with temperature control and frequency variation
- **Intelligent:** Multiple operation modes including: Peak Shaving, Load Shedding, PV-Storage Energy Control, and Frequency Regulation. Operating data can be transmitted to Fox Cloud via Wi-Fi, 4G or 5G.
- **Augmentable:** Capable of parallel connection upgrade for flexible system size application



For more Fox ESS Product info,
please visit www.fox-ess.com



Fox ESS MAX SERIES

MAX-AIO-100/200

Model	MAX-AIO-100/200
Battery Module Data	
Battery Type [V/Ah]	LFP 3.2/280
Battery Pack Capacity [kWh]	53.76
Battery System Capacity [kWh]	215
Operating Voltage Range [V]	627-864
Number of Temperature Sensor	128
AC Output Data	
Rated Output Power [kW]	125
Max.Continuous AC Current [A]	167
THDi [%]	<3
Nominal Grid Voltage [Vac]	480 (3P-N-PE or 3P-PE)
Power Factor	>0.99
Adjustable Power Factor Range	-1~1
Nominal Frequency [Hz]	50/60
System Data	
Round Trip Efficiency [%]	>89
DOD [%]	100
Cycle Life	7000@70%EOL
Communication Interfaces	RS485/Ethernet
Ingress Protection	IP55
Cooling	liquid cooling
Altitude [m]	≤2000
Operation Temperature [°C]	-25~55
Operation Humidity [%]	5~95RH, non-condensing
Noise [db]	<75 @1m
Dimensions [W*D*H][mm]	980*1500*2200
Fire Protection	Aerosol
Weight [Kg]	2500
Grid Code	IEEE1547/UL1741
Safety/EMC	UL1741/FCC class A