



THREE PHASE EPS BOX PRO



Max. input current
(per phase) 63A



Safety



IP65 Rated



Quickly Installation

- Max. input current (per phase) 63A
- PC+ABS ,Robust plastic enclosure IP65
- Easy installation, plug and play
- Applied to residential, commercial solar installations
- Compatible with H3/AIO H3 series
- Automatically switch to Off-Grid state



SPECIFICATIONS

| | |
|--------------|-------------|
| Model | EPS BOX PRO |
|--------------|-------------|

UTILITY SUPPLY

| | |
|--------------------------------|---|
| Rated Voltage | 220 / 380VAC, 230 / 400VAC, 3L / N / PE |
| Rated Frequency | 50 / 60Hz |
| Max. Input Current (Per Phase) | 63A |

INVERTER GRID

| | |
|--------------------------------|---|
| Rated Voltage | 220 / 380VAC, 230 / 400VAC, 3L / N / PE |
| Rated Frequency | 50 / 60Hz |
| Max. Input Current (Per Phase) | 25A |

INVERTER EPS

| | |
|--------------------------------|---|
| Rated Voltage | 220 / 380VAC, 230 / 400VAC, 3L / N / PE |
| Rated Frequency | 50 / 60Hz |
| Max. Input Current (Per Phase) | 25A |

Load

| | |
|---------------------------------|---|
| Rated Voltage | 220 / 380VAC, 230 / 400VAC, 3L / N / PE |
| Rated Frequency | 50 / 60Hz |
| Max. Output Current (Per Phase) | 63A |

Communication Interface

| | |
|----------------|--|
| RS-485 (Meter) | |
|----------------|--|

General Data

| | |
|--|----------------------------|
| Cooling Concept | Natural |
| Installation | Wall-mounted |
| Operating Temperature Range (°C) | -25 ~ +60 (derating at 45) |
| Dimensions (W * H * D) (mm) | 550 * 420 * 140 |
| Dimensions of packing (W * H * D) (mm) | 660 * 530 * 245 |
| Net Weight (kg) | 9.3 |
| Gross Weight (kg) | 11 |
| Ingress Protection | IP65 |

